

# HarnView Interconnect Solutions Private Limited

## Micro D - Solder cup series

### Ordering details



HarnView Interconnect

Coming Soon

Coming Soon

| Part number – Identification  | DMH | N1 | 15 | P | SC | W |
|---|-----|----|----|---|----|---|
| Micro D Series  |     |    |    |   |    |   |
| Basic Part number   |     |    |    |   |    |   |
| <b>Shell material &amp; Temperature:</b>                            |     |    |    |   |    |   |
| N1 - Nickel Aluminium shell with 150°C Potting                      |     |    |    |   |    |   |
| N2 - Nickel Aluminium shell with 200°C Potting (on Special request) |     |    |    |   |    |   |
| <b>Number of contacts:</b>  |     |    |    |   |    |   |
| <b>09, 15, 21, 25, 31, 37, 51DR, 51</b>                             |     |    |    |   |    |   |
| <b>Contact Gender:</b>  |     |    |    |   |    |   |
| P: Male (Pin Contact)   |     |    |    |   |    |   |
| S: Female (Socket contact)  |     |    |    |   |    |   |
| <b>SC - Solder Cup</b>  |     |    |    |   |    |   |
| <b>Hardwares:</b>   |     |    |    |   |    |   |
| NH: No hardware   |     |    |    |   |    |   |
| M: Low profile hex socket head jackscrews (removable)               |     |    |    |   |    |   |
| N: High profile hex socket head jackscrews (removable).             |     |    |    |   |    |   |
| S: Low profile slot head jackscrews (removable).                    |     |    |    |   |    |   |
| T: High profile slot head jackscrews (removable).                   |     |    |    |   |    |   |
| P: Jackposts (removable)  |     |    |    |   |    |   |
| Px: Panel mount Jackpost  |     |    |    |   |    |   |

For panel thickness Replace X with 1 = 0.8 mm, 2 = 1.20 mm, 3 = 1.6 mm, 4 = 2.00 mm, 5 = 2.40 mm